



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE



'Single-family kit for Simplebus 2. Suitable for installation in residential, commercial or office buildings. The kit is supplied pre-programmed and ready to use. The kit consists of 1 flush-mounted Ultra entrance panel art. UT2020/4 with call button art. UT9211M, no. 1 Hands-free Mini series door entry monitor art. 6721W and all the accessories required to create the system.



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE

PRODUCTS IN THE KIT



UT2020/4 SB2 ULTRA AUDIO/VIDEO MODULE, 4 USERS

Audio/video module for Ultra entrance panel for up to 4 users, Simplebus 2 system. Easy to install and configure, thanks to smart call button programming. Twilight sensor for automatic nameplate backlighting power-off during daytime hours. Omnidirectional digital microphone and dual loudspeaker for high-fidelity audio. Wide-angle colour video camera (field of vision: 120° horizontal, 90° vertical) Audio-visual indications for disabled individuals assistance request can be activated via programming. Facility for 2 call buttons. To be finished with a cap, single button or double button in professional-grade plastic given an anti-yellowing and anti-dulling treatment or in aluminium. Regulation and programming without removing the module. Dimensions: 1 Ultra module. ULTRA, the new and most technologically advanced entrance panel offering maximum ease of installation. Available in flush-mounted (10 mm protrusion from the wall) or surface-mounted (just 35 mm protrusion from the wall) variants. Dimensions: 100x90x35 mm

GENERAL DATA	
Type	Modular
Height (mm)	90
Width (mm)	100
Depth (mm)	35
Product color	Aluminium, Black RAL9005, Transparent
Product weight (g)	350
Type of finishing materials	Polycarbonate, Aluminium alloy
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory
COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE

AUDIO FEATURES

Microphone	MEMS audio digital sensor, omnidirectional
Loudspeaker	28mm (Ø), 8 Ohm, 1W (2)
Technologies implemented	Full-Duplex

CAMERA FEATURES

Camera	Colours
Sensor type	1/3" CMOS
Lens optical dimensions (mm)	1.79
Angle of view (H x V - °)	120 x 90
Sensitivity (lux)	0.45
Video resolution (H x V - pixel)	1288x968

ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Absorption in stand-by (W)	1.5
Maximum absorption (W)	6

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	2
Backlight colour	White, Off
Clamps	L L V+ V- COM NC NO SE+ SE-/GND RTE TX- TX+ RX- RX+
Number of inputs (n°)	1
Number of outputs (n°)	2
Type of outputs	Relay (C-NO-NC, 4A@12÷24 VAC/VDC, 10A peak), SE: unlock pulse of 4A, holding current of 200mA for 12VAC / DC locks (maximum impedance 18 Ohm)
Communication ports	Micro-USB



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE

HARDWARE FEATURES

Twilight sensor	Yes
-----------------	-----

SETTINGS

Loudspeaker volume	Yes
Microphone volume	Yes
Backlight brightness	Yes

PROGRAMMING MODE

Manual programming (via Dip Switch)	Yes
ViP Manager software	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP65
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
Number of auxiliary relays (n°)	1
Input for local door release button	Yes
Door open signaling input	Yes
Visual indications of system status	Yes
Acoustic signals of system status	Yes
Speech synthesis of system status	Yes



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE

UT9211M SINGLE METAL ULTRA BUTTON



Single button for Ultra entrance panel. Made with aluminium trim to increase resistance to impact and polymethyl methacrylate treated to increase resistance to UV rays while preventing yellowing and dulling. Double nameplate (blank and with a bell symbol) included. Easy nameplate replacement.

GENERAL DATA	
Height (mm)	22
Width (mm)	95.6
Depth (mm)	7.4
Product weight (g)	20
Type of finishing materials	Polycarbonate, Aluminium alloy
Product color	Aluminium, Transparent

HARDWARE FEATURES	
Call type	Push-buttons
Type of buttons	Mechanical
Backlight colour	White, Off



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE



UT9161 FLUSH-MOUNTING FRAME FOR 1 ULTRA MODULE

Flush-mounting frame, 1 module, for Ultra entrance panel. It consists of a metal support that secures the modules without using screws and a finishing frame in die-cast aluminium given a cathoporesis treatment to increase its resistance to chemical and environmental corrosion, including damage from UV rays. 10 mm protrusion from the wall. Can be used in flush-mounting boxes art. 3110/1 and 3110/1A, with the option of installing several modules side by side. Dimensions: 125,5x136x35mm

COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

MAIN FEATURES	
Height (mm)	136
Width (mm)	125.5
Depth (mm)	35
Product weight (g)	450

GENERAL DATA	
Type of finishing materials	Metallic, Die-cast aluminum
Product color	Black RAL9005, Siver RAL9006

MOUNTING/INSTALLATION	
Flush-mounted	Yes



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE



1210A SIMPLEBUS2 POWER SUPPLY UNIT

Power supply unit for audio or audio/video systems with 1 input compatible with all outdoor entrance panels featuring Simplebus 2 technology and 1 output for the connection of devices such as door-entry phones and door entry monitors featuring Simplebus 2 technology. Supplied with line termination terminal art. 1216.

MAIN FEATURES	
Supply voltage	230VAC / 50÷60Hz
Output supply voltage	33VDC
Applicable to DIN rail	Yes
Number of DIN modules (n°)	8

HARDWARE SPECIFICATIONS	
Product weight (g)	1000

GENERAL DATA	
Height (mm)	62
Width (mm)	143
Depth (mm)	90
Type of finishing materials	Plastic
Product color	White
Operating temperature (°C)	0 ÷ 40

COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Simplebus 2 audio system	Yes

MOUNTING/INSTALLATION	
Wall-mounted	Yes

ELECTRICAL SPECIFICATIONS



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE

Max absorption (W)	30
Maximum current absorption (mA)	350
Maximum power delivered (W)	40



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE



6721W SIMPLEBUS2 MINI HANDSFREE DOOR ENTRY MONITOR

Wall-mounted hands-free monitor with full-duplex audio and 4.3" / 16:9 colour screen. Allows brightness control, plus adjustment of the ringtone volume, which can be customised by choosing one of several different melodies. Equipped as standard with 5 sensitive touch back-lit controls for audio activation, door-opening, self-ignition, switchboard call, privacy service and LED signalling for the door status. Manages floor door calls as standard. Option of adding 3 additional buttons with accessory Art. 6734W. Complete with 2 x 8-position DIP-SWITCH for user code programming and button programming. The wall-mounting or residential series box backplate and riser distribution terminal Art. 1214/2C are included. The monitor can only be used in 2-wire Simplebus2 systems. Dimensions: 115x160x22mm.

GENERAL DATA	
Height (mm)	160
Width (mm)	115
Depth (mm)	22
Product weight (g)	500
Product color	White RAL9003
Type of finishing materials	ABS
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

DISPLAY	
Display size (")	4.3



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE

DISPLAY

Aspect Ratio	16:9
Resolution (pixels)	480x272

AUDIO FEATURES

Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 40 Ohm, 1W
Technologies implemented	Full-Duplex

ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷34 VDC (Bus)
Absorption in stand-by (W)	0.06
Maximum absorption (W)	11.9

HARDWARE FEATURES

Type of buttons	Capacitive
Service buttons	Lock-release, Answer, Silent (Privacy), Door open
No. of programmable buttons for additional functions	2 (5 with accessory art. 6734W)
Clamps	L L CFP1 CFP2
Removable terminals	Yes

SETTINGS

Loudspeaker volume	Yes
Microphone volume	Yes
Ringtone volume	Yes
Screen brightness control	Yes
Screen contrast	Yes
Screen colour	Yes



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 75
Environmental class	I (B1)
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

GENERAL FEATURES

Door opener	Yes
Automatic door opening on call (Doctor)	Yes
Silent mode (Privacy)	Yes
Self Activation	Yes
CPS call	Yes
Intercom calls	Yes
Outside door call input	Yes
Customisable ringtone	Yes
Automatic answer (handsfree)	Yes
Sending alarm calls	Yes
Actuator control	Yes
Multiple address	Yes
Door open signaling	Yes



KVU8190V

ULTRA KIT AND SIMPLEBUS 2 MINI HANDS-FREE



3110/1 1 MODULE FLUSH-MOUNTED BOX FOR ENTRANCE PANEL

Module-holder frame with finishing frame. 1 module. Dimensions 118x118x45 mm

MAIN FEATURES

Height (mm)	118
Width (mm)	118
Depth (mm)	45

GENERAL DATA

Type of finishing materials	Plastic
Product color	Green

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes

MOUNTING/INSTALLATION

Flush-mounted	Yes
---------------	-----

AUDIO/VIDEO FEATURES

Audio system	Yes
Audio/video system	Yes